

HVAC RTV Silicone Sealant

HVAC RTV Silicone Sealant is a superior quality silicone which remains flexible from -40°F to 350°F. Never dries out. Has excellent adhesion to metals and can be used for virtually every HVAC need.

- Cures to 100% silicone rubber
- Resistant to sunlight and weather extremes
- Fast cure, high strength
- Meets the requirements of FDA Regulation No. 21 CFR 177.2600
- Meets the requirements of NSF Standard 51
- Listed by Underwriters Laboratories (UL Listed)



MARS NO.	DESCRIPTION			MARS PACK	CASE QTY.
93249	Silicone sealant	clear	10.1 oz.	12	12
93251	Silicone sealant	white	10.1 oz.	12	12
93252	Silicone sealant	gray	10.1 oz.	12	12
93253	Silicone sealant	clear	2.8 oz.	12	12
93254	Silicone sealant	white	2.8 oz.	12	12

Heat Resistant Silicone

HVAC/R RTV Hi-Temp Silicone Sealant Red is a superior quality silicone which was formulated to perform at temperatures ranging from -40°F to 500°F (-40°C to 260°C) for continuous operation and 550°F (288°C) for intermittent exposure. These features make HVAC/R RTV Hi-Temp Silicone Sealant Red is ideal for use around furnace vent pipes, restaurant hoods and heat exchangers. Used where critical bonding and sealing parts must perform at high temperatures.



- Cures to 100% silicone rubber
- Resists the effects of sunlight and weather extremes
- Fast cure, high strength

MARS NO.	DESCRIPTION			MARS PACK	CASE QTY.
93255	Hi-Temp. silicone	red	10.1 oz.	12	12
93247	Heat resistant silicone	red	2.8 oz.	12	12

Fire Stop Caulk

Red Devil Fire Stop Caulk effectively seals penetration openings against the spread of fire, smoke, toxic gases and water when applied properly.

- A Latex-based, high-solids Fire Stop compound
- No Shrinkage
- Withstands temperatures up to 2000° F and is up to 4 hour fire rated
- Sandable and Paintable
- Meets Fed. Specs ASTM E-814 (UL 1479) and ASTM E-84 (UL 723) and many UL Classifications

Red Devil



MARS NO.	DESCRIPTION			MARS PACK	CASE QTY.
93293	Firestop Caulk,	10.5 FL Oz.- Red		12	

Red Devil Celulon And Acrylic Caulk

Celulon™ plumbing and HVAC adhesive sealant is sometimes preferred over silicone. This easy to apply adhesive sealant adheres to all substances, is paintable, cleans up with water and has no offensive odor. Used to seal A/C ducts and lines. Application temp: 40 ° to 90°F. Service temp: -25° to 200°F.

Red Devil



MARS NO.	DESCRIPTION			MARS PACK	CASE QTY.
93256	Celulon HVAC sealant	clear	10.1 oz.	12	12
93257	Celulon HVAC sealant	white	10.1 oz.	12	12

Red Devil Butyl Sealants

Red Devil's butyl sealant is a high performance rubber-like sealant that is ideal for tough outdoor jobs and below grade applications. (marine usage above waterline) It can be used wherever watertight seal is required. This paintable sealant provides excellent adhesion to most building surfaces including aluminum, stone, wood, brick, fiberglass, plastic, metal, etc. This sealant is ideal for use on window/door frames, aluminum gutters, chimney roofs, concrete foundations etc. Sealant remains rubbery and flexible from 0°F to 225°F after full cure.

Red Devil



MARS NO.	DESCRIPTION			MARS PACK	CASE QTY.
93290	Butyl sealant	white	10.1 oz.	12	12
93291	Butyl sealant	aluminum gray	10.1 oz.	12	12